12.8V 100AH

12.8V 200AH





## Super Points: ONE Battery For Multiple Brand Inverters

#### Long cycle life

Using high-quality hithium hron hosphate hatteries, Á the Ácycle Álife ÁsÁmore Áthan Á6000 Átimes OFÔÁJ€% DOD, Áand kan hae Áised hor Á0-15 kjears

#### Product advantages

#### Intelligent BMS battery protection

Built-in intelligent BMS (battery management system), effectively avoiding overcharge, overdischarge, overcurrent, short-circuit, balance and other problems



#### High quality Grade A+ Prismatic LiFePO4 battery

Higher capacity, higher current, longer life

# LIFEPOLITHEM BATTERY LIFEPOLITHEM BATTERY LIFE DO LITHEM BATTERY LIFE DO LI

#### Good safety performance

Extreme safety test, no fire, no explosion, no leakage

#### Low internal resistance and high current

Low internal resistance of the battery, excellent continuous high current discharge performance

## Key Features

- A GRADE high quality prismatic cells.
- ★ High quality smart BMS.
- ★ Maintenance free & Low self discharge & Fast and efficient charging.
- ★ Bluetooth and LCD Display for intelligent control and monitor.

## Protection


- ★ Over charge detection function
- ★ Over discharge detection function
- ★ Over current detection function
- ★ Temperature protection function
- ★ Short circuit detection function
- ★ Balance function
- ★ Upper computer software monitor

## **Parameters**


Product model	LFPI-12.8V100AH	LFPI-12.8V200AH
Product specification	12.8 <b>V 100</b> Ah	12.8 <b>V 200A</b> h
Nominalvoltage	12.8 <b>V</b>	12.8V
Nominal capacity	100Ah	200Ah
Celltype	A+ Grade LiFePO4	A+ Grade LiFePO4
Standard charge voltage	14.6 <b>V</b>	14.6V
Max charge current	100A	150A
Discharge cut-off voltage	10V	10V
Max discharge current	100A	150A
Parallels function	Support 4 units in series/ 4 units in parallel	
Cycle life	6000 Cycles@1C 90%DOD	
Charge temperature range	-0~60°C	
Discharge temperature range	-20~60°C	
Color	Black	
Dimensions	329*172*214 MM	522*240*218 MM
Weight	15kg	20kg
Installation method	Floor	
Energy	1280WH	2560WH
Months Self Discharge	< 3%	
Efficiency of charge	100%@0.2C	
Efficiency of Discharge	96-99%@1C	
Cells	Prismatic	
Case	ABS	
Teminal	M6	
	IV	10
Certificates	ISO,UL,CEI-021,IEC,0	

## Charging and Discharge curve

Charge and discharge curve @0.5C 25°C




Charge curve @0.5C 25°C



### Cycle Life Curve

Different discharge depth life curves &25℃0.5C



Different discharge depth life curves &40℃0.5C

